

## 🏽 iKey

## DT-5K-FSR

Keyboard with Integrated Force Sensing Resistor

The DT-5K-FSR from iKey® combines a Force Sensing Resistor, an upgraded pointing device that offers improved sensitivity and increased durability, with a 10-key numeric keypad in a ruggedized stainless steel case, providing dual functionality in one compact unit. Its 20 function keys provide user versatility. This keyboard also offers user Windows keys for ease of access to the operating system. Features: 10-Key Numeric Pad 113-Key Functionality 20 Function Keys Integrated Force Sensing Resistor Pointing Device USB and PS/2 Configurations Available

## Product Code DT-5K-FSR

| CERTIFICATIONS    | NEMA 4X UL60950, FCC Part 15 Class B  |
|-------------------|---|
| SHOCK             | 3 x 11 ms pulses of 50g on each of 3 axes   |
| CABLE             | LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-Cable USB  |
| KEY SWITCH        | MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 7.03 oz +/- 1.06 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION         | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST<br>PER AXIS: 3 hours  |
| POWER             | PS2: KEYBOARD: 35mA@5V (from Keyboard port) POINTER: 5mA@5V (from Mouse port) USB: 40mA@5V (from USB port)  |
| COMPATIBILITY     | PS/2 KEYBOARD/POINTER: All Windows Operating Systems USB KEYBOARD/POINTER: All Windows and Macintosh OS   |
| TEMPERATURE RANGE | STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)  |
| WARRANTY          | 1 Year Limited Warranty   |
| HUMIDITY          | 100% Humidity Resistant   |
| DIMENSIONS        | 16.25" x 7.88" x 1.80" (w-h-d) 412.8mm x 200.2mm x 45.7mm   |
| MODEL NUMBERS     | DT-5K-PS2: With PS/2 cable DT-5K-USB: With USB cable  |